



LIGNORA

LUXURY ENGINEERED FLOORING

TECHNICAL SPECIFICATION

ISSUED SEPTEMBER 2026

SIGNATURE COLLECTION

Coffee Oak

Plank — random lengths · European Oak · Classic grade

PRODUCT CODE

LN139




Image for illustration. Oak is a natural material — colour and grain vary from board to board and batch to batch.

WIDTH

125 mm

LENGTH

Random

THICKNESS

14 mm · 3 mm wear

GRADE

Classic



Scan to view this floor online and order a free sample.

SPECIFICATION

WOOD SPECIES European Oak (Quercus robur)	SURFACE Brushed	FINISH Brushed Matt Lacquered
DIMENSIONS 14mm x 125mm x random lengths (RL)	CONSTRUCTION 14mm engineered board, 3mm oak wear layer	GRADE Classic
FORMAT Plank — random lengths	INSTALLATION Glue-down or floating	PACK COVERAGE 1.800 m ² per pack
UNDERFLOOR HEATING Suitable (manufacturer guidance applies)	WARRANTY 25-year structural warranty	

GRADE & CHARACTER

Natural character — visible knots and grain movement, balanced and measured.

BEFORE FITTING

Store packs flat and unopened in the room where they will be laid, with heating at normal living conditions, for at least 48 hours before fitting. Subfloors must be flat, clean and dry. Blend boards from several packs as you lay.

CARE & MAINTENANCE

Lacquered finish: sweep or vacuum regularly and clean with a lightly damp mop and a pH-neutral cleaner made for lacquered wood. Avoid steam mops, standing water and abrasive products.

FITTED BY LIGNORA

Supplied throughout the UK and fitted by our own in-house team — the same fitters on every job. Technical certificates are available on request.

LIGNORA

LN139 · Specification correct at time of issue and subject to change. Confirm details with your written quotation before ordering.

020 8068 2947 · info@lignora.co.uk · lignora.co.uk

LIGNORA LTD · Registered in England and Wales · Company no. 17475129