



SIGNATURE COLLECTION

Walnut Herringbone

Herringbone · American Black Walnut · Select grade

PRODUCT CODE

LN203



Image for illustration. Oak is a natural material — colour and grain vary from board to board and batch to batch.

WIDTH

125 mm

LENGTH

600 mm

THICKNESS

14 mm · 3 mm wear

GRADE

Select



Scan to view this floor online and order a free sample.

SPECIFICATION

WOOD SPECIES American Black Walnut (<i>Juglans nigra</i>)	FINISH UV Oiled	DIMENSIONS 14mm × 125mm × 600mm
CONSTRUCTION 14mm engineered board, 3mm walnut wear layer	GRADE Select	FORMAT Herringbone
JOINT SYSTEM Tongue & groove	INSTALLATION Glue-down	PACK COVERAGE 1.500 m ² per pack
UNDERFLOOR HEATING Suitable (manufacturer guidance applies)	WARRANTY 25-year structural warranty	

GRADE & CHARACTER

Refined with a touch of character — small knots and gentle colour variation.

BEFORE FITTING

Store packs flat and unopened in the room where they will be laid, with heating at normal living conditions, for at least 48 hours before fitting. Subfloors must be flat, clean and dry. Blend boards from several packs as you lay.

CARE & MAINTENANCE

Oiled finish: sweep or vacuum regularly and clean with a pH-neutral soap made for oiled wood floors. Refresh high-traffic areas with a maintenance oil as needed — an oiled floor can be spot-repaired without sanding.

FITTED BY LIGNORA

Supplied throughout the UK and fitted by our own in-house team — the same fitters on every job. Technical certificates are available on request.