



SIGNATURE COLLECTION

Distressed Black

Plank · European Oak · Antique grade

PRODUCT CODE

LN209



Image for illustration. Oak is a natural material — colour and grain vary from board to board and batch to batch.

WIDTH

220 mm

LENGTH

2200 mm

THICKNESS

15 mm · 4 mm wear

GRADE

Antique



Scan to view this floor online and order a free sample.

SPECIFICATION

WOOD SPECIES European Oak (Quercus robur)	SURFACE Distressed, hand-finished	FINISH Hardwax Oiled
DIMENSIONS 15mm x 220mm x 2200mm	CONSTRUCTION 15mm engineered board, 4mm oak wear layer, multi-ply core	GRADE Antique
FORMAT Plank	JOINT SYSTEM Tongue & groove	INSTALLATION Glue-down or floating
PACK COVERAGE 2.904 m ² per pack	UNDERFLOOR HEATING Suitable (manufacturer guidance applies)	WARRANTY 25-year structural warranty

GRADE & CHARACTER

Aged and distressed by hand — strong colour variation and a weathered surface.

BEFORE FITTING

Store packs flat and unopened in the room where they will be laid, with heating at normal living conditions, for at least 48 hours before fitting. Subfloors must be flat, clean and dry. Blend boards from several packs as you lay.

CARE & MAINTENANCE

Oiled finish: sweep or vacuum regularly and clean with a pH-neutral soap made for oiled wood floors. Refresh high-traffic areas with a maintenance oil as needed — an oiled floor can be spot-repaired without sanding.

FITTED BY LIGNORA

Supplied throughout the UK and fitted by our own in-house team — the same fitters on every job. Technical certificates are available on request.