



LIGNORA

LUXURY ENGINEERED FLOORING

TECHNICAL SPECIFICATION

ISSUED SEPTEMBER 2026

TIMELESS LINE

# Hayloft Oak

*Herringbone · European Oak · Classic grade*

PRODUCT CODE

LN396



Image for illustration. Oak is a natural material — colour and grain vary from board to board and batch to batch.

WIDTH

125 mm

LENGTH

600 mm

THICKNESS

14 mm · 3 mm wear

GRADE

Classic



Scan to view this floor online and order a free sample.

## SPECIFICATION

|                                                                |                                                           |                                              |
|----------------------------------------------------------------|-----------------------------------------------------------|----------------------------------------------|
| WOOD SPECIES<br>European Oak (Quercus robur)                   | SURFACE<br>Brushed                                        | FINISH<br>Brushed & Oiled                    |
| DIMENSIONS<br>14mm x 125mm x 600mm                             | CONSTRUCTION<br>14mm engineered board, 3mm oak wear layer | GRADE<br>Classic                             |
| FORMAT<br>Herringbone                                          | INSTALLATION<br>Glue-down                                 | PACK COVERAGE<br>1.8 m <sup>2</sup> per pack |
| UNDERFLOOR HEATING<br>Suitable (manufacturer guidance applies) | WARRANTY<br>25-year structural warranty                   |                                              |

## GRADE & CHARACTER

Natural character — visible knots and grain movement, balanced and measured.

## BEFORE FITTING

Store packs flat and unopened in the room where they will be laid, with heating at normal living conditions, for at least 48 hours before fitting. Subfloors must be flat, clean and dry. Blend boards from several packs as you lay.

## CARE & MAINTENANCE

Oiled finish: sweep or vacuum regularly and clean with a pH-neutral soap made for oiled wood floors. Refresh high-traffic areas with a maintenance oil as needed — an oiled floor can be spot-repaired without sanding.

## FITTED BY LIGNORA

Supplied throughout the UK and fitted by our own in-house team — the same fitters on every job. Technical certificates are available on request.

LIGNORA

LN396 · Specification correct at time of issue and subject to change. Confirm details with your written quotation before ordering.

020 8068 2947 · [info@lignora.co.uk](mailto:info@lignora.co.uk) · [lignora.co.uk](https://lignora.co.uk)

LIGNORA LTD · Registered in England and Wales · Company no. 17475129