



SIGNATURE COLLECTION

Sandy Grey Oak

Plank · European Oak · Classic grade

PRODUCT CODE

LN55



Image for illustration. Oak is a natural material — colour and grain vary from board to board and batch to batch.

WIDTH

220 mm

LENGTH

2200 mm

THICKNESS

14 mm · 3 mm wear

GRADE

Classic



Scan to view this floor online and order a free sample.

SPECIFICATION

WOOD SPECIES European Oak (Quercus robur)	SURFACE Brushed	FINISH Brushed & Oiled
DIMENSIONS 14mm x 220mm x 2200mm	CONSTRUCTION 14mm engineered board, 3mm oak wear layer	GRADE Classic
FORMAT Plank	INSTALLATION Glue-down or floating	PACK COVERAGE 2.904 m ² per pack
UNDERFLOOR HEATING Suitable (manufacturer guidance applies)	WARRANTY 25-year structural warranty	

GRADE & CHARACTER

Natural character — visible knots and grain movement, balanced and measured.

BEFORE FITTING

Store packs flat and unopened in the room where they will be laid, with heating at normal living conditions, for at least 48 hours before fitting. Subfloors must be flat, clean and dry. Blend boards from several packs as you lay.

CARE & MAINTENANCE

Oiled finish: sweep or vacuum regularly and clean with a pH-neutral soap made for oiled wood floors. Refresh high-traffic areas with a maintenance oil as needed — an oiled floor can be spot-repaired without sanding.

FITTED BY LIGNORA

Supplied throughout the UK and fitted by our own in-house team — the same fitters on every job. Technical certificates are available on request.