



SIGNATURE COLLECTION

Natural Oak

Herringbone · European Oak · Classic grade

PRODUCT CODE

LN90



Image for illustration. Oak is a natural material — colour and grain vary from board to board and batch to batch.

WIDTH

90 mm

LENGTH

450 mm

THICKNESS

14 mm · 3 mm wear

GRADE

Classic



Scan to view this floor online and order a free sample.

SPECIFICATION

WOOD SPECIES European Oak (Quercus robur)	SURFACE Brushed	FINISH Brushed & UV Oiled
DIMENSIONS 14mm x 90mm x 450mm	CONSTRUCTION 14mm engineered board, 3mm oak wear layer	GRADE Classic
FORMAT Herringbone	JOINT SYSTEM Tongue & groove	INSTALLATION Glue-down
PACK COVERAGE 1.944 m ² per pack	UNDERFLOOR HEATING Suitable (manufacturer guidance applies)	WARRANTY 25-year structural warranty

GRADE & CHARACTER

Natural character — visible knots and grain movement, balanced and measured.

BEFORE FITTING

Store packs flat and unopened in the room where they will be laid, with heating at normal living conditions, for at least 48 hours before fitting. Subfloors must be flat, clean and dry. Blend boards from several packs as you lay.

CARE & MAINTENANCE

Oiled finish: sweep or vacuum regularly and clean with a pH-neutral soap made for oiled wood floors. Refresh high-traffic areas with a maintenance oil as needed — an oiled floor can be spot-repaired without sanding.

FITTED BY LIGNORA

Supplied throughout the UK and fitted by our own in-house team — the same fitters on every job. Technical certificates are available on request.