



BESPOKE COLLECTION

Dark Chocolate Oak

Bespoke colour · European Oak · Dark tone

PRODUCT CODE

LNB6I6



Image for illustration. Wood is a natural material — colour and grain vary from piece to piece and batch to batch.

PLANK WIDTHS

190 – 320 mm

THICKNESS

15 – 20 mm

WEAR LAYER

4 – 5 mm oak



Scan to view this floor online and order a free sample.

SPECIFICATION

WOOD SPECIES European Oak (<i>Quercus robur</i>)	GRADES Rustic · Character · Prime	FINISH Brushed, oiled or matt lacquered — specified to order
CONSTRUCTION Engineered, multi-ply core; 4–5 mm European oak wear layer	FORMATS Plank and herringbone; chevron on request	INSTALLATION Fully bonded (recommended); secret nailed; floated on underlay
UNDERFLOOR HEATING Suitable for underfloor heating systems	SOURCING Made in Britain · FSC & PEFC certified	WARRANTY 25-year structural warranty

SIZES BY LAYING PATTERN (THICKNESS / WEAR LAYER)

BUILD	PLANK WIDTHS	PLANK LENGTHS	HERRINGBONE BLOCKS
15/4 mm	190 · 260 mm	600–1900 · 600–2800 mm	70×350 · 90×450 · 100×600
20/5 mm	320 mm	1200–3200 mm	—

GRADE & CHARACTER

Bespoke colours are finished to order, so the depth of tone can be tuned to match an existing floor or a reference. Each grade shows the same colour differently: Rustic with lively knots, Character balanced, Prime clean and near-uniform. Always approve a sample of your chosen grade and finish before ordering.

BEFORE FITTING

Store packs flat and unopened in the room where they will be laid, with heating at normal living conditions, for at least 48 hours before fitting. Subfloors must be flat, clean and dry. Blend boards from several packs as you lay.

CARE & MAINTENANCE

Sweep or vacuum regularly and clean with a lightly damp mop and a pH-neutral wood floor cleaner. Avoid steam mops, standing water and abrasive products.

FITTED BY LIGNORA

Supplied throughout the UK and fitted by our own in-house team — the same fitters on every job. Technical certificates are available on request.